



### **DESCRIPTION**

The ELP-HWSH extends the ELP-SH family look with an attractive high wattage emergency light featuring a thermoplastic housing, soft rounded corners and adjustable square heads. Available in 6 V and 12 V models and up to 54 W for powering remote heads.

### **APPLICATION**

Suitable for use in commercial and industrial applications where higher light levels are required or remote head capability is desired.

### **ACCESSORIES**

ERH36 – Emergency Remote Head PAR36 for indoor use. Available in 6V, 9W and 12V, 9W versions.

ERHW36 – Emergency Remote Head Weatherproof PAR36 for outdoor use. Available in 6V and 12V version, 8W and 12W versions.

### **APPROVALS**

UL924.  
Life Safety NFPA 101.  
UL listed for damp locations use.

### **HOUSING**

The housing is made of injection molded thermoplastic. It has high impact resistance and is UL94-5V rated.

### **MOUNTING**

The back mounting plate has a molded in universal J-Box mounting pattern and keyhole slots. Knockouts are available on the top, back and sides for easy wire entry.

### **HEADS**

Two attractive square shaped heads with rounded corners are adjustable allowing the end user to direct the light where it will be most useful. Vacuum metalized reflectors increase light output from the heads.

### **ELECTRICAL/BATTERY**

- Dual voltage input 120/277 VAC, 60 Hz.
- Maintenance free, Sealed Lead Calcium batteries with a maximum full recharge time of 24 hours.
- Low voltage disconnect of the battery prevents deep discharge and maintains good battery life.
- Brownout detection circuit will turn on emergency light during low voltage conditions.
- Fully automatic, solid state charger.
- Test switch with LED charge indicator/AC voltage indicator.
- Line latching feature prevents the unit from turning on during installation to a non-energized AC circuit. Saves labor since the installer does not have to return to connect the battery terminals once the building is energized.

Catalog Number	Lamp Type	Lamp Volts	Lamp Watts	Maximum Wattage (for 90 min.)	Weight (Lbs)	Volume (cu. ft.)	Pieces Per Master Carton	Pieces Per Skid
ELP-HWSH-627	T-5 Incan.	6	2 x 9	27 W	7.3	0.53	4	140
ELP-HWSH-654	T-5 Incan.	6	2 x 9	54 W	11.5	0.53	4	140
ELP-HWSH-1254	T-5 Incan.	12	2 x 9	54 W	11.5	0.53	4	140