



### DESCRIPTION

The FT is a general purpose Floodlight for 1000W lamps. It has a wide beam distribution pattern allowing it to be used in almost any floodlighting application where a large amount of light is needed. U.L. listed for wet locations.

### APPLICATION

Suitable for lighting large open areas such as parking lots, storage yards, construction sites, marinas, industrial areas and around buildings. Can also be used for lighting large facades.

### HOUSING

The housing is made of high pressure die cast aluminum and finished in a dark bronze polyester powder coat paint finish for lasting corrosion resistance.

### BALLAST

High Power Factor, Constant Wattage Autotransformer ballasts. Multi Tap (120/208/240/277V) or 480V ballasts. Minimum starting temperature is -40°F (-40°C) for HPS and -20°F (-30°C) for MH.

### SOCKET

Mogul base, 4KV pulse rated porcelain socket.

### MOUNTING

Die cast aluminum slipfitter with dark bronze polyester powder coat paint finish. For use with 2 3/8" - 3" O.D. tenons. Also available in Trunnion and Yoke versions.

### REFLECTOR

Die formed, anodized aluminum.

### GASKET

Silicone rubber for long life.

### LENS

Clear tempered glass, impact and heat resistant.

### EPA

Effective Projected Area at 45° tilt is 2.74

### CATALOG NUMBER LOGIC

**FT-**

**Product Series**  
FT = Floodlight  
Thousand Watt

**MH**

**Lamp Type**  
HP = High Pressure  
Sodium  
MH = Metal Halide

**1000-**

**Lamp Wattage**  
(HPS) 1000  
(MH) 1000

**MT-**

**Voltage**  
MT = Multi Tap  
120/208/240/277V  
480V = 480V

**SF-**

**Mounting**  
SF = Slipfitter  
TR = Trunnion  
YK = Yoke

**L**

**Lamp**  
L = Lamp  
Included

### OPTIONS

FT-WG – Wire Guard  
FT-GS – Glare Shield

FT-VS – Vandal Shield  
FT-BF – Full Baffle

PC-XXX – Button Photocell (XXX = specify voltage)  
PCTL-XXX Twist Lock receptacle and photocell (XXX = specify voltage)