



DESCRIPTION

The VSMD is a 12" x 12" Vandal Resistant Surface Mounting fixture for up to MP 200W or Induction 80W lamps. It has a deeper lens than the VSM fixture allowing for the higher wattage lamps. Its rugged die cast aluminum housing and tough polycarbonate lens make it ideal for high abuse, vandalism prone areas. U.L. listed for wet locations.

APPLICATION

Suited for public areas such as underpasses, parking garages, cold storage rooms, building perimeters, schools, corridors and stairwells.

The Induction 80W version makes an ideal energy saving and long life alternative to traditional MH 175W or MP 150W canopy lights for parking garage applications.

HOUSING

The housing is made of high pressure die cast aluminum and finished in a dark bronze polyester powder coat paint finish for lasting corrosion resistance.

BALLAST

High Power Factor, Constant Wattage Autotransformer ballasts, Multi Tap (120/208/240/277V) ballasts. The minimum starting temperature is -20°F (-30°C) for MP.

SOCKET

Medium base, 4KV pulse rated porcelain socket for HID lamps.

REFLECTOR

Die formed cold rolled steel with a high reflectance white polyester powder coat paint finish.

GASKET

Silicone rubber for long life.

LENS

Tough injection molded polycarbonate for extra impact resistance. UV stabilized. Deeper lens for cooler operation of MP 200W and Induction 80W lamps.

CATALOG NUMBER LOGIC

VSMD-

Product Series

VSMD = Vandal Resistant
Surface Mount
Medium
Deep Lens

ID

Lamp Type

MP = Metal Halide
Pulse Start
ID = Induction

80-

Lamp Wattage

(MP) 200
(ID) 80

120V-

Voltage

MT = Multi Tap
120/208/240/277V
120V = 120V
277V = 277V

L

Lamp

L = Lamp
Included