



### DESCRIPTION

The WPW is a compact low wattage wall pack designed for up to 100W HID lamps or 1 x 42W quad tube fluorescent lamps. Its prismatic polycarbonate or glass lens hides the lamp image making this product suitable for lower mounting heights. U.L. listed for wet locations.

### APPLICATION

Ideal for security lighting around commercial, industrial and residential buildings where lower mounting heights are available. Can be used in entranceways, walkways and for perimeter lighting around buildings.

### HOUSING

The housing is made of high pressure die cast aluminum and finished in a dark bronze polyester powder coat paint finish for lasting corrosion resistance.

### BALLAST

High Reactance, High Power Factor ballasts for MH Lamps and High Power Factor, Reactor ballasts for HPS lamps. Electronic ballasts for Fluorescent 1x26, 32 or 42W in 120V.

### SOCKET

Medium base, 4KV pulse rated porcelain socket for HID lamps. Positive latching thermoplastic socket for fluorescent lamps.

### MOUNTING

Knockout pattern provided on back casting for mounting to junction boxes. Three 1/2" threaded entry hubs provided for top or side conduit wiring and through wiring.

### GASKET

Silicone rubber for long life.

### LENS

Prismatic polycarbonate refractor for uniform distribution at low mounting heights. Glass lens for MP 100W version.

### CATALOG NUMBER LOGIC

**WPW-**

**Product Series**  
 WPW = Wall Pack Wedge

**HP**

**Lamp Type**  
 MP = Metal Halide Pulse Start  
 HP = High Pressure Sodium  
 FL = Fluorescent quad tube

**100-**

**Lamp Wattage**  
 (MP) 50, 70, 100  
 (HPS) 35, 50, 70, 100  
 (FL) 126 = 1 x 26W  
 132 = 1 x 32W  
 142 = 1 x 42W

**120V-**

**Voltage**  
 MT = Multi Tap  
 120/208/240/277V  
 120V = 120V  
 DT = 120/277V

**L**

**Lamp**  
 L = Lamp Included

### OPTIONS

WPW-WG – Wire Guard for WPW fixture.  
 WPW-GS – Glare Shield for WPW fixture.  
 PC-XXX – Button Photocell (XXX = specify voltage).