



DESCRIPTION

The WPW is a compact low wattage wall pack designed for up to 100W HID lamps or 1 x 42W quad tube fluorescent lamps. Its prismatic polycarbonate or glass lens hides the lamp image making this product suitable for lower mounting heights. U.L. listed for wet locations.

APPLICATION

Ideal for security lighting around commercial, industrial and residential buildings where lower mounting heights are available. Can be used in entranceways, walkways and for perimeter lighting around buildings.

HOUSING

The housing is made of high pressure die cast aluminum and finished in a dark bronze polyester powder coat paint finish for lasting corrosion resistance.

BALLAST

High Reactance, High Power Factor ballasts for MH Lamps and High Power Factor, Reactor ballasts for HPS lamps. Electronic ballasts for Fluorescent 1x26, 32 or 42W in 120V.

SOCKET

Medium base, 4KV pulse rated porcelain socket for HID lamps. Positive latching thermoplastic socket for fluorescent lamps.

MOUNTING

Knockout pattern provided on back casting for mounting to junction boxes. Three ½" threaded entry hubs provided for top or side conduit wiring and through wiring.

GASKET

Silicone rubber for long life.

LENS

Prismatic polycarbonate refractor for uniform distribution at low mounting heights. Glass lens for MP 100W version.

CATALOG NUMBER LOGIC

WPW-

Product Series
 WPW = Wall Pack Wedge

HP

Lamp Type
 MP = Metal Halide Pulse Start
 HP = High Pressure Sodium
 FL = Fluorescent quad tube

100-

Lamp Wattage
 (MP) 50, 70, 100
 (HPS) 35, 50, 70, 100
 (FL) 126 = 1 x 26W
 132 = 1 x 32W
 142 = 1 x 42W

120V-

Voltage
 MT = Multi Tap
 120/208/240/277V
 120V = 120V
 DT = 120/277V

L

Lamp
 L = Lamp Included

OPTIONS

WPW-WG – Wire Guard for WPW fixture.
 WPW-GS – Glare Shield for WPW fixture.
 PC-XXX – Button Photocell (XXX = specify voltage).